

## Description

This double-sided tape consists of a polyester film carrier which is layered on both sides with different adhesives. The adhesive on the covered side of the tape has excellent permanent adhesive qualities. The adhesive on the open side allows easy removal from many surfaces. The adhesive is lined with a double sided siliconised paper.

## Carrier

Polyester film, 23 micron

## Liner

Siliconised paper, white, 90 g/m<sup>2</sup>

## Adhesive

Covered side: rubber; open side: modified dispersion acrylate

## Area of use

This tape is especially suitable for the installation of carpets at conferences or exhibitions (with high cohesion and easy removal). Not appropriate for porous stone or marble.

## Technical Data

<b>Thickness*</b> (adhesive + carrier)	190 micron
<b>Temperature resistance***</b>	-40° C to +70° C
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	Covered side: after 1 min: 40 N/25 mm after 20 min: 40 N/25 mm after 24 h: 42 N/25 mm  Open side: after 1 min: 4 N/25 mm after 20 min: 5 N/25 mm after 24 h: 7 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	Covered side: at 23° C >240 h Open side: at 23° C >120 h
<b>Shelf life**</b>	1 year
<b>Application temperature</b>	> +18° C

\* average

\*\* in original packaging, at 20° C and 50% relative humidity

\*\*\* normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.