



The brand new RX series of cutting plotters is available in four sizes, 61cm, 101cm, 132cm, and 183cm. Designed With a stylish appearance and new functional features, the RX series is the top notch cutter in the market for professional sign makers.

Compatible with Windows 2000/ XP/ Vista/ 7/ 8 and MAC OS X 10.4-10.

Spec RX series RX-61 RX-101S RX-132S RX-183S Operational Method Roller-Type Max. Cutting Width 610 mm (24") 1016mm (40") 1320mm (52") 1830 mm(72") Max. Cutting Length 50 m (164 ft) Max. Media Loading Width 810 mm (31.88") 1635 mm (64.37") 2145 mm (84.44") 1326 mm (52.2") 300 mm (11.8") Min. Media Loading Width 50 mm (1.97") Number of Pinch Rollers 2 3 5 0.8 mm (0.03") Acceptable Material Thickness Drive Motor DC Servo Control Cutting Force 5 ~ 600 g Max. Cutting Speed 1530 mm/sec (60 ips) (at 45° direction) Acceleration 4.2 G (gravity) Offset 0~1.0 mm (with an increase of 0.025 mm) Memory Buffer 16 MB Interfaces USB 2.0 (Full Speed) and Serial (RS-232) Type of Command HP-GL, HP-GL/2 Mechanical Resolution 0.006 mm 0.025 mm Software Resolution Distance Accuracy ±0.254 mm or ±0.1% of move, whichever is greater USB 2.0 (Full Speed) and Serial (RS-232) Interfaces Type of Command HP-GL, HP-GL/2 Mechanical Resolution 0.006 mm Software Resolution 0.025 mm Distance Accuracy ±0.254 mm or ±0.1% of move, whichever is greater Repeatability ±0.1 mm Automatic-Aligning System Completely Automatic Contour Cutting System for print to cut solution Curve & Arc Smoothing Yes Configurable Origin Yes Test Cut capability Yes Tangential mode Yes Over Cut Yes Repeat Yes Сору Pouncing Yes Control Panel LCD (20 digits x 2 lines), 15 Keys, 1 Power LED, 1 Green LED 100~240 VAC 50 / 60 Hz (auto switching) Power Supply Power Consumption 251.8 watts

Dimension (HxWxD) mm 274.2 * 1098 * 273.5 1149 * 1614 * 606 1149 * 1923 * 606 1149 * 2433 * 760 (HxWxD) in 10.8 * 43.2 * 10.8 45.2 * 63.5 * 23.8 45.2 * 75.7 * 23.8 45.2 * 95.8 * 29.9 Net Weight 25 kg (55 lb) 61.8 kg (136.2 lb) 71.5 kg (157.6 lb) 87.2 kg (192.2 lb)

Auto Cut off Standard

Stand 1Optional Standard

Media Basket Optional

15° C~30° C / 60°F~86° F Temperature Operation Environment Humidity 25% ~ 75%