

Technical parameters

Model Item	GC-24	GC-48	GC-24S	GC-48S
Drive System	Stepping motor		Servo motor	
Max.paper width	740mm	1310mm	740mm	1310mm
Max.plotting width	640mm	1210mm	640mm	1210mm
Interface	Serial port & USB port			
Language Format	DMPL / HPGL			
Max. plotting speed	800mm/s		1200mm/s	
Max. cutting force	500g			
Cutting Tool	Imported hardness alloy steel blade			
Power supply	AC90V~AC240V			
Operation Environment	Temperature:5℃~35℃		Relative humidity:(30%-50%)without condensation	
Net weight	12.6kgs	28kgs	12.6kgs	28kgs
Packing size	100×35×40cm	160×35×40cm	100×35×40cm	160×35×40cm
Colors	White color, grey color, black color			

Features

- Forward and reverse paper feeding supported.
- GC cutting plotter adopts imported stepping motors, low noise gritting roller and better electromagnetic carriage, contribute to precise cutting; GCS employs imported servo motors, featuring high speed, excellent precision and low noise.
- Chinese, English, German, French, Spanish supported.
- Popular European style large size screen with backlight contributes to easy operation.
- RS-232 port and USB port with hot plug function is available.
- It is configured with large memory, red light position system, manual outline cutting.
- Compatible with Windows XP, Windows Vista, Windows7 (32 bit and 64 bit)