

## ОФИЦИАЛЕН ПРЕДСТАВИТЕЛ ЗА БЪЛГАРИЯ

гр.Пловдив 4003, ПК 100, ул.“Ибър” №31, тел. 032/94 58 85, факс: 96 07 99, info@microasu.com

25мм цилиндрични паралели  
водят гредата.



Алуминиева гредка с място за  
подрездане на инструменти.



## Ламинатори FY- 1325 / 1530 / 1537 / 1737



Незалепващ силиконов вал 130мм  
с голяма термоустойчивост и  
трайност. Работна маса от 10мм  
закалено стъкло с LED осветление  
подобрява точността на монтажите.  
До 50мм максимална дебелина.



В комплект с компресор за повдигане/спускане на вала.  
Това осигурява лесна работа и равномерен натиск.



Със система за поставяне на ролки  
в предната и задната част на  
машината.



## Технически данни

Item	Flatbed laminator			
Model	FY1325	FY1530	FY1537	FY1737
Diameter of roller:	130mm			
Material of rollers:	Silicon dioxide Feature:thermostability,wear-resisting,anti-aging,moisture proof, Good elasticity,pollution-free,No Distortion			
Max.effective working size:	1300mm*2500mm	1500mm*3000mm	1500mm*3700mm	1700mm*3700mm
Table glass:	10mm temper glass			
Illumination	LED tube illumination			
Guideways	25mm cylinder guideways,very steady for long time use			
Machine frame	Steel high temperature weld table,steel strong legs and Aluminium profile around the table and bridge			
Machine paint	Sprayed finished			
Material roll holder	In front and at behind durable material reels support			
Max.filming thickness	50mm			
Roller heating:	Internal heating by infrared			
Temperature range	Adjustable,environmental-120°C			
Warm up time	10-15min			
Power Consumption	0.8~1.0kw/h			
Power consumption	2500w			
Laminating mode	Manual			
Pressure adjustable mode	Pneumatic/non-noise air compressor			
Input Frequency	50-60 hz			
Rated input voltage	110v/220v			
Net weight of machine	6600kg			