

# LG Hausys

## sign & graphic materials

**LP3912/LP3942**

Polymeric Protective Laminate



Dated: 7.2012

# LG Hausys

sign & graphic materials

## LP3912/LP3942

Polymeric Protective Laminate

Type	LP3912	LP3942
<b>Production</b>	Electro cut, hand cut, kiss cut, die cut	
<b>Application Period</b>	Medium term applications	
<b>Colors</b>	Transparent	
<b>Adhesive</b>	Pressure sensitive, transparent, permanent, acrylic based.	
<b>Film Coat</b>	PVC	
<b>Production Process</b>	Polymeric calendered	
<b>Thickness</b>	0.09 mm	
<b>Service Temperature Range</b>	-45 °C – +82 °C	
<b>Application Temperature</b>	Minimum +10 °C	
<b>Durability</b>	5 years	
<b>Removability</b>	Permanent	Removable
<b>Compatible Products</b>	Compatible with the base films LD3911 /391T, LD393T, LD3950/LD395T, LD3920 and LD4910.	



**LG Hausys Europe GmbH**  
 Lyoner Straße 15, ATRICOM C6  
 60528 Frankfurt am Main  
 Germany  
 Phone: 0049 69 -58 30 29 441  
 Fax: 0049 69 -66 11 35 06  
 Email: sign@lghausys.eu  
 Web: <http://sign.lghausys.eu/en>