

Series	Description	Typical Application	Standard Size		Extension Factor of UV Protection	Colors / Finish	Thickness	Adhesive	Release Liner
			width	length					
200	2 Year Economy PVC Film	Economy laminate, indoor and outdoor protection.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+1 years	Transparent/ G, SG, M	2.5 mil	Clear, water-based, permanent	Silicone-coated 53# paper
210	4 Year PVC Film	Indoor and outdoor protection. Ideal for medium-term graphics. Flat application ONLY.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+2 years	Transparent/ G, SG, M	2.5 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
215	5 Year PVC Film	Indoor and outdoor protection. Ideal for medium- to long-term graphics. Flat application ONLY.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+3 years	Transparent/ G, SG, M	2.75 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
240	7 Year Polyvinyl Fluoride Film	Anti-graffiti film. Designed for high-quality protection of large-format digital prints in outdoor applications.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+5 years	Transparent/ High Gloss	1 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
250 AS	2 Year PVC Film	Suitable for indoor floor graphics protection. Recommended for Series 1663 film. Meets ASTM D 2047 & BAM StVo /35 d3	36", 40", 50", 54"	164 (50 meters)	Not Applicable	Transparent/ Raised Non-Skid Texture	4.5 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
255 AS	2 Year PVC Film	Suitable for indoor protection of floor graphics exposed to very high loads. Meets ASTM D 2047 & BAM StVo /35 d3	36", 40", 50", 54"	164 (50 meters)	Not Applicable	Transparent/ Raised Non-Skid Texture	6.5 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
290	8 Year Premium PVC Cast Film	Recommended for indoor and outdoor conformable fleet and other large graphic applications.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+4 years	Transparent/ G, M	2 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper
290 F	8 Year Optically Clear PVC Cast Film	Recommended for protection of Series 3675 and Series 3676 perforated Window Graphic Films.	24", 30", 36", 40", 50", 54", 60"	164 (50 meters) 10 meters	+4 years	Transparent/ G, M	2 mil	Clear, solvent-based, permanent	Silicone-coated polyester film 1.4 mil
293	8 year Ultra Flexible Cast Film	Recommended for protection of Series 3551/3551RA and Series 5600.	30", 36", 40", 50", 54", 60"	164 (50 meters)	+4 years	Transparent/ G, M	1 mil	Clear, solvent-based, permanent	Silicone-coated 53# paper

NOTE: Rated outdoor life expectancy based on accepted application procedures and vertical surface exposure.

Product Series	RECOMMENDED LAMINATES									
	ORAGUARD® 200	ORAGUARD® 210	ORAGUARD® 215	ORAGUARD® 240	ORAGUARD® 250 AS	ORAGUARD® 255 AS	ORAGUARD® 290	ORAGUARD® 290F	ORAGUARD® 293	
395I				■			■	■	■	
395IRA				■			■	■	■	
3880			■							
3850			■							
355I			■	■			■	■	■	
355IRA			■	■			■	■	■	
369I		■	■							
3676								■ ■		
3675								■ ■		
365I		■ ■	■							
364I	■ ■	■								
3640	■ ■	■								
3628		■ ■								
362I	■ ■	■								
3620	■ ■	■								
3165		■ ■	■							
3165RA		■ ■	■							
3164	■ ■	■								
3109		■	■							
1663					■	■				
5600							■	■	■	

Match Recommended Laminate to Application by Color

Applications using 395I/395IRA laminated with 293 are recommended for highly experienced vehicle wrap installers **ONLY.

■ FLEET/VEHICLE GRAPHICS
■ SHORT-TERM PROMOTIONAL

■ P.O.P./EXHIBIT
■ OUTDOOR SIGNAGE & BANNERS

■ BACKLIT SIGNAGE
■ WINDOW GRAPHICS-ARCHITECTURAL

■ FLOOR GRAPHICS
■ TRANSIT

For the most up to date information log on to our website at www.oracal.com

1100 Oracal Parkway • Black Creek, GA 31308 • Toll Free 888-672-2251 • 912-851-5000 • Fax 912-851-5060