LG Hausys sign & graphic materials

LA 8082N

Translucent Matte Cast Vinyl

Description

LA 8082N is a high performance translucent cast vinyl designed for corporate identifications, fleet marking applications and various sign graphics. It offers exceptional value for applications that require extended durability.

Application:

- Interior displays, signs, corporate identifications and fleet marking
- Point-of-purchase or exhibition stands
- Window decoration

Features

- Surface film: Translucent & matte Cast PVC film
- Adhesive: Solvent, clear permanent acrylic
- Release Liner: Double side olefin coated Paper / kraft Paper
- Available width: 48"(1,220mm)
- Durability: 3 yearsShelf Life: 1 years

Cutting

• Electro cut/Hand cut/Kiss cut/Die cut

Characteristics

Property	Result
Film thickness	110 µm ± 10 (Including adhesive)
Tensile strength	Min 0.5kg/cm²
Elongation at break	Max. 25%
Adhesion (24 hours)	Min. 1.200g/inch
Adhesive Thickness	0.03mm
Release Liner	Double sides PE coated paper (140μ m, $\pm 10\%$)
Dimensional stability (DIN30646)	Max. 0.5%
Temperature resistance	-25 ℃ ~ 82 ℃
Minimum application temperature	≥10℃



14-12-17 LA8082N Update: 2014-12-17

LG Hausys sign & graphic materials

Warranty:

The information provided on this sheet represents typical properties and does not constitute a specification. No liability will be accepted for errors and omissions and in no circumstances shall LG chem. Ltd be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet. All LG chem. Vinvl sold are subject to our conditions of sale. LG chem. Also retains the right to change sizes and specifications of products without prior notice.



14-12-17 LA8082N Update: 2014-12-17 Page 2 of 2