

Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



BRICK

Description Very thick PU plotter cut material, with polyester backing, available with matt or glossy finish.

> Despite the outstanding thickness, the material grants easy cutting, weeding and application and a high washing resistance. Suitable for cotton, polyester, performance wear, poly/cotton blends

and spandex, not treated or dye sublimated **Usage** Preheat the lower press plate for 15 seconds at 155°C.

Due to thickness it is possible to cut letters of 2 cm height minimum.

- · Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- · Remove the carrier cold

For glossy colors GOLD and SILVER:

- Heat apply at the conditions shown on the right
- Remove the carrier cold
- Cover with silicon paper or teflon and press again for 5 seconds

Washing Wait at least **24 hours** from application before washing.

Washing resistance up to 60°C, best inside-out.

Do not use bleach or other aggressive chemical agents.


Not suitable for dry cleaning.

Suitable for tumble dry, cotton program.

The product is REACH compliant

The product is certified Öko-Tex® Standard 100 Class II

Average thickness 1000 microns



Blade: 60° Pressure: 150 gf Speed: 10 cm/sec



Transfer settings

25 seconds at 155°C (310°F) medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer





N.B. All information here contained are based on our experience.

We recommend to perform a test before starting standard production.

For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

