

STRIPFLOCK®

PRODUCT

INFORMATION

Description	Plotter cut flock heat seal material with polyester backing. Average film thickness before application: 500 micron
Basic information	Due to the many different base materials available on the market, the following instructions are given as a guideline only : Plotter settings (eg. with SUMMACUT D60 – ROLAND GX24) Blade: high thickness blade Minimum required pressure: 100 gf Transfer setup Temperature: 160°C (320°F) Time: 15 " Pressure: medium (3÷4 bar)
Application instructions	N.B.: with special colors Cinnamon, Denim, Orchid and Emerald, we highly recommend cutting details not smaller than 1 cm Mirror cut the material. We recommend using high thickness blades. Weed the exceeding material Place the material on the garment with its polyester backing Heat apply Remove the support cold

Suitable textiles	Cotton, polyester and blends of these materials (not suited for treated and dye sublimation fabrics)
Washing instructions	Wait 24h after the heat transfer 60°C Max Do not use bleach or other aggressive chemical agents. Dry clean: no Tumble dry: yes



Siser s.r.l.

N.B.
All information given in this sheet are based on our experience.
We always recommend performing a test before starting standard production.
For best results we recommend to store the product away from direct sunlight.

Viale della Tecnica nº 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - www.siser.it

r.e.a. vi 171856 - reg. imp. vi n° 14971 c.s. € 103.300 i.v.-p.iva 01591490246 The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.it. For further information, please contact our Sales Office. Thank you.