

## VIDEOFLEX MODA

**Description** PVC plotter cut heat seal material with polyester backing, transparent or transparent w/ glitters.  
Average film thickness before application: **300 micron**

**Basic information** Due to the many different base materials available on the market, the following instructions are given as a guideline only :  
Plotter settings (eg. with SUMMACUT D60 – ROLAND GX24)  
Blade: **high thickness blade**  
Minimum required pressure: **120 gf**  
**Transfer setup**  
Temperature: **150°C (300°F)**  
Time: **15"**  
Pressure: **medium (3÷4 bar)**

### Application instructions

Mirror cut the material  
Weed the exceeding material  
Place the material on the garment with its polyester backing  
Heat apply  
Remove the support cold

---

**Suitable textiles** Cotton, polyester and blends of these materials  
(not suited for treated and dye sublimation fabrics)

**Washing instructions** Wait **24h** after the heat transfer  
**40°C Max**  
Do not use bleach or other aggressive chemical agents.  
Dry clean: **no**  
Tumble dry: **not recommended**



**Siser s.r.l.**

Viale della Tecnica n° 18  
36100 Vicenza - Italy  
Tel. +39 0444.287960  
Fax +39 0444.287959  
info@siser.it - www.siser.it

r.e.a. vi 171856 - reg. imp. vi n° 14971  
c.s. € 103.300 i.v. - p.iva 01591490246

N.B.

All information given in this sheet are based on our experience.  
We always recommend performing a test before starting standard production.  
For best results we recommend to store the product away from direct sunlight.

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).  
This document can be subject to variations. Updated versions are available on our website [www.siser.it](http://www.siser.it).  
For further information, please contact our Sales Office.  
Thank you.