



# COLORPRINT® NEW M

## SPECIFICATIONS

| Composition | Average Thickness | Carrier                | Certifications   |
|-------------|-------------------|------------------------|--|
| PVC         | 120 microns       | non adhesive polyester | REACH n° 1907/2006/EU<br>  |

## APPLICATION INSTRUCTIONS

| APPLIES ON  | SUGGESTED CUTTING SETTINGS |          |           | TRANSFER SETTINGS |               |                      |      |
|---|----------------------------|----------|-----------|-------------------|---------------|----------------------|------|
| cotton, polyester, poly/cotton blends<br>(not suited for treated and dye sublimated textiles) | Blade                      | Pressure | Speed     | Time              | Temperature   | Pressure             | Peel |
|   | 45°                        | 50 gf    | 30 cm/sec | 15 seconds        | 165°C (329°F) | Medium (2,5/3,5 bar) | hot  |

- Print, cut and peel off excess material
- Remove the print from the carrier with the help of TTD Easy
- Place the decoration on the fabric
- Apply following the recommended parameters
- Remove the TTD while hot

### PRODUCT HIGHLIGHTS

- Thin material
- Matte finish

**NOTE:** Given the large numbers of inks and printers, we highly recommend a test before launching a production

## CARE AND WASHING RECOMMENDATIONS

| Washing                     | Ironing             | Tumble dry | Dry cleaning | Storage Shelf Life | Storage Temperature   | Storage Conditions          | Position |
|-----------------------------|---------------------|------------|--------------|--------------------|-----------------------|-----------------------------|----------|
| Up to 60°C, best inside-out | YES best inside-out | NO         | NO           | Up to 2 years      | Between 18°C and 26°C | Away from sunlight and dust | Vertical |

- Wait 24 hours after the application before the first wash
- Respect the textile recommendations
- Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on [www.siser.com](http://www.siser.com)  
For further information, please contact our sales office: [info@siser.it](mailto:info@siser.it)



Siser s.r.l.  
Viale della Tecnica, 18  
36100 Vicenza - Italy

Tel. +39 0444.287960  
Fax +39 0444.287959  
[info@siser.it](mailto:info@siser.it)  
[www.siser.com](http://www.siser.com)

r.e.a. vi 171856  
reg. imp. vi n° 14971  
c.s. € 103.300 i.v.  
p.iva 01591490246



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9105027958

