



CopyFUN Grey

www.basicpaper.com

Transfer Instructions with Mug Press – Mug-O-Matic

- 1 Print on the unprinted side of CopyFUN transfer. (mirror image).
- 2 Unprinted area can be cut off before transferring the image. **Leave a 3 mm border.**
- 3 Stick the Grey transfer using heat-resistant tape on the mug (not on the image and leaving a 3 mm border).
- 4 For 72 mm mug place special CopyFUN 72 mm Mug Adaptor.
- 5a Mug-O-Matic: Place the mug with the Teflon sheet in the press.
- 5b Mug Press: Place the mug with the transfer + rubber band + Teflon (exterior) in the press.
- 6 Close the press, **175°C /350°F**, transfer time 3 minutes.
- 7 Remove the transfer paper after 5 minutes. (The mug is still warm)
- 8 Place the mug in a pre-heated oven for 5 minutes at 200 °C. *
- * The image will be glossy and the pottery will be dishwasher-proof after it has been in the oven.

Transfer instructions with commercial heat press - Wood • Cardboard • Metal • Aluminium

- 1 Copy on the unprinted side of the CopyFUN transfer. (mirror image).
- 2 Unprinted area can be cut off before transferring the image. **Leave a 3 mm border.**
- 3 Position the Grey transfer using heat-resistant tape on wood, cardboard, metal or aluminium.
- 4a Metal and aluminium 120 seconds WITH A-pad.
- 4b Wood and cardboard without A-pad for 5 seconds.
- 5 Remove the transfer paper after 5 minutes. (The material is still warm)

Storage

- Allow the transfers 12 to 24 hours to acclimatise to your room temperature. *Always* store transfers in a box or plastic cover. Store in a dry and cool place. The transfers can be kept for 3 years.

Important

- We aim to deliver an optimal product. All our transfers are therefore tested on the most common copiers/printers. We cannot however, guarantee that this product will be appropriate for every type of copier/printer. We recommend that you test the appropriateness and quality of your combination of equipment and transfers prior to production. We cannot be held responsible for any direct or indirect damage and/or injury that may ensue from the use or attempted use of this product.



CopyFUN Grey	Mug Press Mug with Sublimation coating	Mug Press Mug with toner transfer coating	Manual Mug Press Mug with toner transfer coating	Heat Press Tiles, wood, cardboard, metal, aluminium
Product				
Teflon sheet		Yes		Yes
Silicone rubber mat		Yes		Yes
Temperature	Up to 200°C	175°C /350°F	200°C	215°C
Time	Count down 3 minutes	3 minutes	5 Minutes	90 Seconds
Peal	Put in bucket of water and peel cold	Remove the transfer paper after 5 minutes. (The mug is still warm)	Remove the transfer paper after 10 minutes. (The mug is still warm)	Remove the transfer paper when still warm
Remark	Print 1200 x 600 Dpi	Print 1200 x 600 Dpi	Print 1200 x 600 Dpi	Place the material TURNED with the transfer down wards on the Teflon sheet in the press.

Download your complete compatibility list for Printers-Copiers in PDF format: www.basicpaper.com

CopyFUN Grey video instructions, visit: www.basicpaper.com