

## WINDOW CLING PRODUCT SERIES

## WF200-

## MICRO-TAC AIRFREE WHITE FILM

1. Automatical wetting on the certain window
2. Perfect Transperant
4. Non PVC Solvent Coating

NaturaMedia is introducing and launching Window Cling Film series as of 2015 y'.

This film is one of top high quality products among Natura Window Cling films, especially special adhesive.

Base film is Poly Propylene with removable for indoor window decoration.

This special adhesive is easy to stick on and easy to remove. It can be used correct as many times as you need.

Not using glue, so there is no sticky feeling and does not leave any glue on the surface.

## \* Cautions

Before printing, hangle this film with gloves to avoid marks during printing.

Not suitable for unflatness surface.

Not recommended for outdoor usage.

For indoor using, do not need water for small space installing.

Adhesion side may be particularly vulnerable to UV rays.

## APPLICATION

Window Decoration

ROAD SHOP Window Advertisement

Fashion, Sports, Electronics, Veichle, Deli, Coffee, Etc.

INDOOR Window Advertisement

Conference rooms, Lobbies, Retail identification signs

Residential interiors, Office Privacy, Glass partitions.

## SPECIFICATION

Caliper	295 micron (11.8 mil)
weight	280g/m <sup>2</sup>
Surface	MATT
Base Material	Poly Propylene
Width	50"
Length	30m (100 ft)
Core	3"

## COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility

Solvent-Based / UV-Curable

## TECHNICAL DATA

Caliper	295 micron	ASTM D645
Gloss	60° : 15.0 / 85° : 30.0	ASTM D2457
L.a.b	90.0 / 0 / -5.0	ANSI T (D50/2 <sup>9</sup> /Abs/No)

## GUIDELINES

Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%

Use care in handling printed material, surface susceptible to abrasion

To optimize the printing quality, printer need to be set for highest print quality.

**Printable with Latex, but a bit curled after printing.**

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment

Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life:

About one year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

## Application

### ROAD SHOP Window Advertisement

**Fashion** Full Color  
Wall cover  
Reverse  
Inside



**Sports & Coffee** Full Color  
Wall cover  
Reverse  
Inside



**Furniture** Full Color  
Etched  
Reverse  
Inside



### INDOOR Window APPLICATION

**Conference room & POS** Full Color  
Reverse  
Inside

