

Description

Double sided adhesive transparent polyester film, also available with double sided covering as 4032D

Release paper

White silicone coated PE paper on both sides, 100 g/m², 4032 D with white silicone coated paper 135 g/m² and 98 g/m²

Adhesive

Covered side: Solvent polyacrylate, removable

Area of use

Mounting film for self-adhesive equipment of smooth surfaces. The removable adhesive guarantees residueless removal within 2 years of outdoor application.

Technical data

Thickness* (without protective paper and adhesive) 12 micron

Temperature resistance adhered to aluminium -40°C to +120°C, no variation

Adhesive power* 2 N/25 mm/11 N/25
(FINAT TM 1, after 24h, stainless steel,
covered side/open side)

Shelf life** 2 years

Application temperature min. +8°C

* average ** in original packaging, at 20°C and 50% relative humidity

Attention:

Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure respectively. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore the application informations published by ORAFOL are to be considered.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

