

## Description

This double-sided tape consists of a polyester film carrier, layered on both sides with modified solvent acrylate adhesives of different strengths. The adhesive on the open side has very strong bonding characteristics as well as resistance to high temperatures and moisture. The adhesive on the covered side allows easy, residueless removal from many surfaces.

## Carrier

Polyester film, 12 micron

## Liner

Brown paper, both sides coated with silicone, 90 g/m<sup>2</sup>

## Adhesive

Covered side: modified solvent acrylate, removable  
Open side: modified solvent acrylate, permanent adhesive

## Area of use

Especially suitable as a self-adhesive medium for different materials. Ideal for situations where easy and residueless removal is required.

## Technical Data

<b>Thickness*</b> (adhesive and carrier)	100 micron		
<b>Temperature resistance***</b>	-40° C to +120° C		
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)		open side	covered side
	after 1 min:	16 N/25 mm	1,0 N/25 mm
	after 20 min:	18 N/25 mm	1,2 N/25 mm
	after 24 h:	20 N/25 mm	1,5 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)		open side	covered side
	at 23° C:	> 500 h	>48 h
	at 70° C:	> 72 h	1 h
<b>Temperature resistance*</b> (S.A.F.T.)	95° C		
<b>Shelf life**</b>	2 years		
<b>Application temperature</b>	> +15° C		

\* average    \*\* in original packaging, at 20°C and 50% relative humidity    \*\*\* 1h, normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.