



## **CWT 1640 Premium**



\*Applicator shown in the pictures is CWT Regular with Premium upgrade kit. FACTS

	CWT 164010
PART NO	CWT 164011
CAPACITY UP TO	140 m2/h (1500sq. ft./h)
TABLE LENGTH	4000mm (13ft. 1.4in.)
TABLE WIDTH	1600mm (5ft. 3in.)
LENGTH OF WORKING AREA	3560mm (11 ft. 8in.)
WIDTH OF WORKING AREA/ROLLER WIDTH	1560mm (5ft. 1.5in.)
OVERALL WIDTH	1810mm (5ft. 11 in.)
OVERALL HEIGHT	1620mm (5ft. 4in.)
MAX. THICKNESS OF SUBSTRATE	0-70mm (0-2.8in.)
WORK HEIGHT	776-944mm (2ft. 6.5in3ft. 1.1in.)
WORK HEIGHT ADJUSTEMENT*	Manual
BED SURFACE	Tempered safety glass
POWER SUPPLY	230V/50Hz (10A)/120V/60Hz (15A)
REQUIRED AIR SUPPLY	6-8bar (87-116psi)
NET WEIGHT	533kg (1175lbs)
GROSS WEIGHT	692kg (1525lbs)
PACKING DIMENSIONS	4940x560x2100 mm (16ft. 2.4in. x 1.8ft. 10in. x 7ft. 1in.)

## FEATURES

CUTTING MAT, SELF HEALING	Yes
ROLL HOLDER FOR GLIDE BEAM	Yes
LED ILLUMINATED LIGHT TABLE	Yes
EXTRA LOWER ROLL HOLDER	Yes
TABLE TOP ROLL HOLDER	Yes
SIDE POCKETS	Yes
SILENT COMPRESSOR	Option
SECOND GLIDE BEAM	Option
WHEELS	Yes
LEVELING FEETS	Yes

<sup>\*</sup> Select 1 of 4 fixed heights at installation.