



CWT 1647 Premium



*Applicator shown in the pictures is CWT Regular with Premium upgrade kit.



See cwtworktools.com for complete model program and accessories.

FACTS

PART NO	CWT 164710 CWT 164711
CAPACITY UP TO	150 m ² /h (1600sq. ft./h)
TABLE LENGTH	4700mm (15ft. 5in.)
TABLE WIDTH	1600mm (5ft. 3in.)
LENGTH OF WORKING AREA	4260mm (14ft.)
WIDTH OF WORKING AREA/ROLLER WIDTH	1560mm (5ft. 1.5in.)
OVERALL WIDTH	1810mm (5ft. 11in.)
OVERALL HEIGHT	1620mm (5ft. 4in.)
MAX. THICKNESS OF SUBSTRATE	0-70mm (0-2.8in.)
WORK HEIGHT	776-944mm (2ft. 6.5in.-3ft. 1.1in.)
WORK HEIGHT ADJUSTEMENT*	Manual
BED SURFACE	Tempered safety glass
POWER SUPPLY	230V/50Hz (10A)/120V/60Hz (15A)
REQUIRED AIR SUPPLY	6-8bar (87-116psi)
NET WEIGHT	628kg (1384lbs)
GROSS WEIGHT	813kg (1792lbs)
PACKING DIMENSIONS	4940x560x2100 mm (16ft. 2.4in. x 1.8ft. 10in. x 7ft. 1in.)

FEATURES

CUTTING MAT, SELF HEALING	Yes
ROLL HOLDER FOR GLIDE BEAM	Yes
LED ILLUMINATED LIGHT TABLE	Yes
EXTRA LOWER ROLL HOLDER	Yes
TABLE TOP ROLL HOLDER	Yes
SIDE POCKETS	Yes
SILENT COMPRESSOR	Option
SECOND GLIDE BEAM	Option
WHEELS	Yes
LEVELING FEET	Yes

* Select 1 of 4 fixed heights at installation.

"FINISHING WHAT YOU STARTED"