ULTRAFIT WINDOW FILM

VIVID FORTE Series

VLT 7%
TSER 65%
IR REJECTION 84%

VF 05 BK

First Class Sustainability

Maintaining an average of 80% in the solar infrared ray test spectrometer (750nm – 2500nm), the **Vivid Forte** meets the high standards of the market today to display its creditability to our clients.

SPECIFICATIONS	
Visible Light Transmission	7 %
Visible Light Reflection (Int) / (Ext)	6 % / 5 %
UV Rejection	99 %
IR Rejection	84 %
Solar Heat Gain Coefficient	0.35
Shading Coefficient	0.40
Total Solar Energy Rejection	65 %

AUTOMOTIVE FILMS

HAZE ★★★★
SAFETY ★★
FADE OUT ★★★★★
SHIRINKAGE ★★★★
UV BLOCK ★★★★★
BLOCKS HEAT ★★★★★

INOGROW

ULTRAFIT WINDOW FILM

VIVID FORTE Series

VLT 18%
TSER 61%
IR REJECTION 81%

VF 15 BK

First Class Sustainability

Maintaining an average of 80% in the solar infrared ray test spectrometer (750nm – 2500nm), the **Vivid Forte** meets the high standards of the market today to display its creditability to our clients.

SPECIFICATIONS	
Visible Light Transmission	18 %
Visible Light Reflection (Int) / (Ext)	6 % / 5 %
UV Rejection	99 %
IR Rejection	81 %
Solar Heat Gain Coefficient	0.39
Shading Coefficient	0.45
Total Solar Energy Rejection	61 %

AUTOMOTIVE FILMS

HAZE ★★★★
SAFETY ★★
FADE OUT ★★★★★
SHIRINKAGE ★★★★
UV BLOCK ★★★★★
BLOCKS HEAT ★★★★★

INOGROW

ULTRAFIT WINDOW FILM

VIVID FORTE Series

VLT 35%
TSER 50%
IR REJECTION 78%

VF 35 BK

First Class Sustainability

Maintaining an average of 80% in the solar infrared ray test spectrometer (750nm – 2500nm), the **Vivid Forte** meets the high standards of the market today to display its creditability to our clients.

SPECIFICATIONS	
Visible Light Transmission	35%
Visible Light Reflection (Int) / (Ext)	8 % / 7 %
UV Rejection	99 %
IR Rejection	78 %
Solar Heat Gain Coefficient	0.49
Shading Coefficient	0.57
Total Solar Energy Rejection	50 %

AUTOMOTIVE FILMS

HAZE ★★★★
SAFETY ★★
FADE OUT ★★★★★
SHIRINKAGE ★★★★
UV BLOCK ★★★★★
BLOCKS HEAT ★★★★

INOGROW

ULTRAFIT WINDOW FILM

VIVID FORTE Series

VLT 53%
TSER 44%
IR REJECTION 65%

VF 50 BK

First Class Sustainability

Maintaining an average of 80% in the solar infrared ray test spectrometer (750nm – 2500nm), the **Vivid Forte** meets the high standards of the market today to display its creditability to our clients.

SPECIFICATIONS	
Visible Light Transmission	53 %
Visible Light Reflection	7 %
UV Rejection	99 %
IR Rejection	65 %
Solar Heat Gain Coefficient	0.56
Shading Coefficient	0.64
Total Solar Energy Rejection	44 %

AUTOMOTIVE FILMS

HAZE ★★★★
SAFETY ★★
FADE OUT ★★★★★
SHIRINKAGE ★★★★
UV BLOCK ★★★★★
BLOCKS HEAT ★★★★

INOGROW

ULTRAFIT WINDOW FILM

VIVID FORTE Series

VLT 71%
TSER 38%
IR REJECTION 67%

VF 70

First Class Sustainability

Maintaining an average of 80% in the solar infrared ray test spectrometer (750nm – 2500nm), the **Vivid Forte** meets the high standards of the market today to display its creditability to our clients.

SPECIFICATIONS	
Visible Light Transmission	71 %
Visible Light Reflection(Int)/(Ext)	7 % / 7 %
UV Rejection	99 %
IR Rejection	67 %
Solar Heat Gain Coefficient	0.66
Shading Coefficient	0.74
Total Solar Energy Rejection	38 %

AUTOMOTIVE FILMS

HAZE ★★★★
SAFETY ★★
FADE OUT ★★★★★
SHIRINKAGE ★★★★
UV BLOCK ★★★★★
BLOCKS HEAT ★★★★

INOGROW