


BF600 BACKLIT FRONT MATTE WR 215

DETAILS

- Printable with Dye, Pigment, UV and Latex with incredibly deep blacks and vibrant colors
- Translucent polyester backlit film with outstanding color expression
- Provides wide color gamut and vivid color with light
- Bright and bluish surface for excellent printing quality
- Provides even diffusion of light

SPECIFICATIONS

Length (m)	30	Width (inch)	36" 50" 60"
Weight (g/m ²)	270	Coating	Porous
Caliper (um)	215	Base Material	PET
Inner Core (inch)	3	Printer	
Surface	Matte		

KEY FEATURES

- Wide color gamut and vivid color with light
- Outstanding color expression
- Highest ink limit
- Bright and bluish surface
- Even diffusion of light

APPLICATION

- Lightbox advertising, Illuminated displays, Trade show and exhibition graphics & Signage
- Special Backlit application
 - Cosmetics
 - Fashion image
 - Air Port & great image application

GENERAL INFORMATION

- Printer Profiles are available at HP Media Locator : hp.com/go/mediasolutionslocator
- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Lamination is optional.
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature

※ Cautions

- When using with HP Latex 300 series, recommended to be cautious about white spot caused by bubble and deformation caused by drying heat. (Recommend to adjust ink quantities or delay the printing speed : increase the pass and delay offset value)
- Recommended to be cautious about white spot caused by residue stayed in the printner : Proper cleaning is required.
- Recommended to check and adjust the feeding when having problem with banding caused by slip.