

WINDOW CLING PRODUCT SERIES

SO830-- SOLVENT-BASED

SOLVENT SEMI-TAC CLEAR WINDOW FILM

This is ultra transparent, reversable, re-positionable, and easily removed without residue.
Transparent polyester film with self transparent adhesion for Eco Solvent, LATEX, UV-Curable Printing.
The main printing advantages are the highest contrast and excellent gradation.

Window graphics are a great, low cost solution when you need to expand your signage without taking up floor or wall space.
Used as temporary point of sale(POS), Promotional graphics draw the attention of passers with sales literature.
A variety of colour and photographic images can be used to promote specific products and services on your windows.
It uses road and outside shop fronts and be part of indoor window wall displays

APPLICATION

Window Decoration & POS
Eye-catching advertisements.
ROAD SHOP Window Advertisement
Fashion, Sports, Electronics, Veichle, Deli, Coffee, Etc
Indoor Window Advertisement
Conference rooms, Lobbies, Retail identification signs
Residential interiors, Office Privacy, Glass partitions and cubicles
Appliances, Casings (e.g. white goods)

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility

ECO-SOL	LATEX	UV
---------	-------	----

Printer Compatibility

HP, EPSON, MIMAKI, ROLAND, MUTOH, Seiko, OCE, Vutek

SPECIFICATION

Caliper	180 micron (7.2 mil)
weight	250g/m ²
Surface	ULTRA Transparent (Clear)
Base Material	Clear Polyester
Width	50"
Length	30m (100 ft)
Core	3"

TECHNICAL DATA

Caliper	180 micron	ASTM D645
Gloss	Transparent	ASTM D2457
L.a.b	Transparent	ANSI T (D50/2°/Abs/No)

GUIDELINES

Printing Tip	Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60% Use care in handling printed material, surface susceptible to abrasion To optimize the printing quality, printer need to be set for highest print quality.
Lamination:	Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.
Storage:	It is recommended to store in the closed original packing in a cool and dry environment Temperature 10~25°C (50~77°F), Relative Humidity 50% RH
Shelf Life:	One year stored in original package in recommended condition


Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

Application

ROAD SHOP Window Advertisement

Fashion

Full Color
Wall cover
Reverse
Inside



Sports & Coffee

Full Color
Wall cover
Reverse
Inside



Furniture

Full Color
Etched
Reverse
Inside



INDOOR Window APPLICATION

Coference room & POS

Full Color
Reverse
Inside

